

Tiling for showroom / after-sales reception



Description

- Anthracite grey (RAL 7016).
- Dimensions: 45 x 45 cm or 60 x 60 cm.
- Thickness: 9.5 mm.
- Supplier: CASALGRANDE / NOVOCERAM
- Ref. NO NAME - C828 - ELEGANCE.

Skirtings

- Dimensions: 8 x 45 cm (minimum).
- Thickness: 9.5 mm
- Ref. Straight, NONAME - C860 - ELEGANCE

Variants

- For stricter regulations, class R10 slip-resistance is available (Type: SORANO by CASALGRANDE).



TILING
ALABAMA



PANTONE 433
RAL 7016

Layout recommendation

- New vehicle showroom, new vehicle delivery, after-sales reception.
- Lay with double bonding, including joint bonding.
- Tiles must all be laid the same way round with the direction of the fibre perpendicular to the main facade.
- The joints must be a colour equivalent to RAL 7016 anthracite grey.

Routine maintenance advice

- Use a quaternary ammonium-based solution (ammonia solution or traditional detergent such as AJAX, VIGOR, etc.).
- Follow the concentrations given in the technical specifications of the products used.
- Where possible use a single-disc scrubbing machine (medium/hard disc). There are separate washing and rinsing tanks.
- Once a month, wash with an acid solution to remove limescale from rinsing water.

Tiling for Renault Minute workshop



Description

- Through-coloured stoneware tiles.
- Dimensions: 20 x 20 cm, thickness: 11.3 mm.
- Supplier: CASALGRANDE / NOVOCERAM
- Ref. ALABAMA black-grey (Novoceram).

Skirtings

- Straight ALABAMA, Dimensions: 10 x 20 cm, thickness: 11.3 mm.

Layout recommendation

- Renault Minute workshop.
- Lay with double bonding, including joint bonding.
- Skirting joints must be aligned with floor tiling joints.
- Traditional tiling using mortar is also possible but requires highly qualified operators and is therefore not recommended.



TILING
ALABAMA



PANTONE 433
RAL 7016

Routine maintenance advice

- Use a quaternary ammonium-based solution (ammonia solution or traditional detergent such as AJAX, VIGOR, etc.).
- Follow the concentrations given in the technical specifications of the products used.
- Where possible use a single-disc scrubbing machine (medium/hard disc). There are separate washing and rinsing tanks.
- Once a month, wash with an acid solution to remove limescale from rinsing water.